

EMI SUPPRESSION RIBBON CABLE CORES

Series DE




APPLICATIONS

- EMI suppression generated from ribbon cable used in digital equipment.

PRODUCT IDENTIFICATION

DE **15** **B** **08** **B** **S** **200R**
a b c d e f g

- a : Type of products - EMI Suppression Ribbon Cable Cores
b : Length (mm) - 15 = 15.4 ± 0.4 , 20 = 20 ± 0.5 , 29 = 29.2 ± 0.6 , 28 = 28 ± 0.6
33 = 33.3 ± 0.8 , 30 = 30 ± 0.8 , 24 = 24 ± 0.6 , 29 = 29.7 ± 0.6
c : Color - B = Black W = White
d : Width (mm) - 08 = 8.4 ± 0.3 , 10 = 9.9 ± 0.3 , 14 = 14.4 ± 0.4 , 15 = 15 ± 0.4
16 = 16 ± 0.4 , 17 = 16.4 ± 0.4 , 18 = 18.7 ± 0.4 , 13 = 14 ± 0.4 , 26 = 25.9 ± 0.7
e : Packing (PCS / REEL) - B = Bults
f : Tolerance - S = $\pm 25\%$
g : Impedance - 200R = 200 Ω



SHAPES & DIMENSIONS & ELECTRICAL CHARACTERISTICS

Parts Number	Dimensions (Unit : mm)				Impedance (Ω)		Remark	Fig.
	A	B	C	D	25MHz	100MHz		
DE15□08BS200R	8.4 ± 0.3	4.35 ± 0.3	3.8 ± 0.15	15.4 ± 0.4	80	200	LF-35BR	1
DE20□10BS205R	9.9 ± 0.3	5.1 ± 0.3	5.3 ± 0.15	20.0 ± 0.5	85	205	LF-50BR	1
DE29□14BS240R	14.4 ± 0.4	7.7 ± 0.3	7.6 ± 0.20	29.2 ± 0.6	130	240	LF-75GR	1
DE28□15BS275R	15.0 ± 0.4	7.5 ± 0.3	6.6 ± 0.20	28.5 ± 0.6	125	275	LF-65BS	2
DE28□16BS270R	16.0 ± 0.4	7.6 ± 0.3	9.0 ± 0.30	28.0 ± 0.6	150	270	LF-80BR	1
DE33□17BS270R	16.4 ± 0.4	8.3 ± 0.3	9.3 ± 0.20	33.3 ± 0.8	150	270	LF-90BR	1
DE30□18BS290R	18.7 ± 0.4	9.4 ± 0.3	10.2 ± 0.3	30.0 ± 0.8	130	290	LF-100BS	2
DE24□13BS100R	14.0 ± 0.4	12 ± 0.4	11.4 ± 0.3	24.0 ± 0.6	50	100	TF-120BR	3
DE29□26BS300R	25.9 ± 0.7	13 ± 0.4	13 ± 0.3	29.7 ± 0.6	140	300	LF-130BS	2

CURVE

